

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
27 January 2005 (27.01.2005)

PCT

(10) International Publication Number
WO 2005/007522 A3

(51) International Patent Classification⁷: **B65D 5/12, 3/10**

(21) International Application Number:
PCT/US2004/022114

(22) International Filing Date: 12 July 2004 (12.07.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
60/486,160 10 July 2003 (10.07.2003) US

(71) Applicant (for all designated States except US): **MEAD-
WESTVACO CORPORATION** [US/US]; One High
Ridge Park, STAMFORD, CT 06905 (US).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **GELARDI, John A.**

[US/US]; P.O. BOX 714, Rocky Pasture, Kennebunkport,
ME 04046 (US). **MAZUREK, Richard** [US/US]; 1031
Roseland Avenue, Huntingdon, PA 19006 (US).


(74) Agents: **DREW, Michael, V et al.; MEADWESTVACO
CORPORATION**, 299 Park Avenue, 13th Floor, New York,
NY 10171 (US).

(81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,
ZW.

(84) Designated States (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,

[Continued on next page]

(54) Title: TUBULAR CONTAINER WITH SEPARATE ENDCAP



(57) Abstract: A container includes a tube (20) having a rim at one end defining an opening and an endcap (40,80) including a channel that is shaped to receive the tube rim. The tube includes at least one latching aperture (30,32) positioned such that when the tube rim is seated in the channel, the latching aperture is contained within the channel. The endcap further includes a latching member (44) that engages the latching aperture when the tube rim is seated in the receiving channel. The latching member includes a sloped surface (62) for deflecting the tube rim to allow the tube rim to be slid into position over the latching member. The endcap further includes a first guide fin assembly (46) on a first side of the latching member and a second guide fin assembly (48) on a second side of the latching member. Each of the first and second guide fin assemblies includes a sloped surface shaped to deflect the tube rim in a direction opposite to the deflection of the tube rim by the latching member when the tube rim is slid into position in the channel, and to maintain the engagement of the latching aperture by the latching member when the tube rim is seated in the channel.

WO 2005/007522 A3



GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

(88) Date of publication of the international search report:
10 March 2005

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Published:

— with international search report